



NB Two Ram



For all recycling grades and NF metals



Key Features:

Stamper Option ~ for enhanced automatic baling for difficult to shear materials

Easy to operate controls

Optimal hydraulic operating pressures

Bellevue, Ohio
800-843-7512
www.americanbaler.com

NB Two Ram Series

Models: N520, N620
Bale Size: 60" x 30" x 45"
Feed Opening: 74" x 43";
82" x 43" (long side-no stamper)
Main Cylinder: 10" bore trunnion design
Main Ram Penetration: Deep penetration into bale chamber
System Pressure: 3000 psi
Main Motor: 50, 75, Twin 50 or Twin 75 HP
Feed Type: Conveyor, loader
Wire Tying: Accent 470;
Plastic strapping optional
Shear: Serrated blade standard (straight blades optional)
Door: Combination bale release and bale separation door
Optional: Hydraulic stamper at the shear
Meets all current ANSI 245.51 Safety Standards

PRODUCTION OPTIONS

12.4 Ton Hydraulic Stamper
Tool steel shear blades: straight ram/serrated beam blades for MSW & NF metals applications
Open operator platform above charge box w/ stairs & railing
Operator platform and enclosure with heat & AC
Nema 4 upgrade
Power unit located other than position #1
Accent-Enviro Bale System
Plastic strapper in lieu of standard wire strapper
Power Unit Cover
Increased Cooling Capacity: Recommended for ambient temperatures above 100 Degrees F, Required for ambient temperatures above 110 Degrees F
Panel heaters both panels



Distributed By: