



WB Two Ram



For all recycling grades and NF metals



Key Features:

Stamper Option ~ *for enhanced automatic baling for difficult to shear materials*

Easy to operate controls

Optimal hydraulic operating pressures

Bellevue, Ohio
800-843-7512
www.americanbaler.com

WB Two Ram Series

Models: W721, W828

Bale Size: 60" x 30" x 45"

Feed Opening: 87" x 60",
110" x 60" (long side-no stamper)

Main Cylinder: 12" bore trunnion design

Main Ram Penetration: Deep penetration into
bale chamber

System Pressure: 3000 psi (W721),
3500 psi (W828)

Main Motor: Twin 50, Twin 75 HP,
or Triple 75 HP (Model W828 only)

Feed Type: Conveyor, loader

Wire Tying: Accent 470 standard;

Plastic strapping optional

Shear: Serrated blade standard
(straight blades optional)

Door: Combination bale release and bale
separation door

PRODUCTION OPTIONS

18.8 Ton Hydraulic Stamper1

Tool steel shear blades: straight ram/serrated
beam blades for MSW & NF metals applications

Open operator platform above charge box w/
stairs & railing

Operator platform and enclosure with heat & AC

W828: Upgrade to flooded inlet power unit
(T75HP) W828: Upgrade to flooded inlet power
unit (225HP)

Nema 4 upgrade

Power unit located other than position #1

Accent-Enviro Bale System

Plastic strapper in lieu of standard wire strapper

Power Unit Cover

Increased Cooling Capacity: Recommended for
ambient temperatures above 100 Degrees F,

Required for ambient temperatures above 110
Degrees F

Panel heaters both panels



Distributed By: